



# FLAT CABLES

## -FRW/2-



RoHS  
COMPLIANT  
2002/95/EG

### GENERAL CHARACTERISTICS

This cable is suitable for connecting table lamps or light electrical appliances .  
Not to be used as power cable.

### CABLE STRUCTURE

Conductors: flexible conductors in bare copper or copper clad aluminium (CCA).

Insulation: Flat cable with two conductors coupled side by side, insulated with fire resistant PVC.

CODE	SEC. NOM. (mm <sup>2</sup> )	DIMENSION (mm)	COLOR
PCS035O	2 x 0,35	2 x 4,2	GOLD
PCS050O	2 x 0,50	2,1 x 4,3	GOLD
PCS10O	2 x 1	2,4 x 5	GOLD
PCS035A	2 x 0,35	2 x 4,2	SILVER
PCS050A	2 x 0,50	2,1 x 4,3	SILVER
PCS10A	2 x 1	2,4 x 5	SILVER
PCS035M	2 x 0,35	2 x 4,2	BROWN
PCS050M	2 x 0,50	2,1 x 4,3	BROWN
PCS075M	2 x 0,75	2,3 x 5	BROWN
PCS035N	2 x 0,35	2 x 4,2	BLACK
PCS050N	2 x 0,50	2,1 x 4,3	BLACK
PCS075N	2 x 0,75	2,3 x 5	BLACK
PCS10N	2 x 1	2,4 x 5	BLACK
PCS035B	2 x 0,35	2 x 4,2	WHITE
PCS050B	2 x 0,50	2,1 x 4,3	WHITE
PCS075B	2 x 0,75	2,3 x 5	WHITE
PCS10B	2 x 1	2,4 x 5	WHITE

Standard packing: 100m shrink wrapped coils



# FLAT CABLES

## -POLARIZED-



RoHS  
COMPLIANT  
2002/95/EG

### GENERAL CHARACTERISTICS

Flat twin polarized conductors, suitable for HI-FI equipments.

### CABLE STRUCTURE

**RN items:** two bare copper conductors or copper clad aluminium (CCA).

**PL items:** one bare copper and one tinned copper.

Insulation: Flat cable with two conductors coupled side by side, insulated with fire resistant PVC.

CODE	SECTION. (mm <sup>2</sup> )	DIMENSION (mm)	COLOR
PCS035RN	2 x 0,35	2 x 4,35	RED / BLACK
PCS050RN	2 x 0,50	2,4 x 4,8	RED / BLACK
PCS075RN	2 x 0,75	2,5 x 5	RED / BLACK
PCS10RN	2 x 1	2,6 x 5,2	RED / BLACK
PCS15RN	2 x 1,5	2,7 x 5,6	RED / BLACK
PCS25RN	2 x 2,5	3,45 x 6,75	RED / BLACK
PCS075PL	2 x 0,75	2,5 x 5	POLARIZED
PCS10PL	2 x 1	2,6 x 5,2	POLARIZED
PCS15PL	2 x 1,5	2,7 x 5,6	POLARIZED

Standard packing: 100m shrink wrapped coils